



				FENDER STRIP							
				Black UV stable P.V.C. Working temperature range -25°C to +80°C. Supplied in 25m coils.							
				A	B	C	D	E	F	G	H
5444/001				Weight 13.5kg/29.8lb							
METRIC (mm)				56.0	19.0	22.0	44.0				
IMPERIAL (ins)				2.21	0.75	0.87	1.73				

				ALUMINIUM CARRIER							
				Supplied in 4m lengths.							
				A	B	C	D	E	F	G	H
5444/002				Weight 1.8kg/4lb							
METRIC (mm)				43.5	22.0	10.5					
IMPERIAL (ins)				1.71	0.87	0.40					

				END CAPS							
				Black finish.							
				A	B	C	D	E	F	G	H
5444/003				Polycoated aluminium				Weight 30g/1.1oz			
5444/004				Plastic				Weight 10g/0.4oz			
METRIC (mm)				71.5	26.0	19.0	68.5	16.0			
IMPERIAL (ins)				2.82	1.02	0.75	2.70	0.63			



DOUBLE 'D' FENDER	
Fender = Black marine grade neoprene.	
Strip = Marine grade stainless steel, with Ø5 mm	
Fixing holes at approx. 79 mm (3.11") centres.	
Optional black PVC insert is available to cover both strip & screw heads for 7666/103, 104 & 105.	

FENDER	WIDTH	STAND-OFF	COIL LENGTH	COIL WEIGHT	END MOULDINGS	CORNER MOULDINGS
7666/101	22mm (0.875")	14mm (0.562")	36.5m (120')	13.8kg (30.5lb)	/	/
7666/102	32mm (1.25")	16mm (0.625")	30m (100')	20kg (44.5lb)	/	/
7666/103A	38mm (1.5")	13mm (0.5")	36.5m (120')	20.7kg (45.7lb)	7666/003	/
7666/103	45mm (1.75")	19mm (0.75")	30.5m (100')	27.5kg (60.7lb)	7666/002	/
7666/104	51mm (2")	25mm (1")	18.3m (60')	28.8kg (63.6lb)	7666/124	/
7666/105	60mm (2.375")	32mm (1.25")	12.2m (40')	30.6kg (67.6lb)	7666/015	7666/005