



PERFECTVIEW

COLOUR SYSTEM WITH LED SUPPORT

A cost effective package consisting of a compact 5" TFT colour monitor plus an exterior camera with LED support and infra-red lighting for excellent night time visibility.

The system switches on automatically when reverse gear is engaged, but it can also be activated manually.

The camera has an integrated microphone, which can be used to give the driver instructions from outside the vehicle - audible to the driver via the monitor's speaker.

Dual video inputs on the monitor allows use of either a second exterior camera or even a DVD player.

9634/250

PERFECTVIEW COLOUR SYSTEM

Includes monitor, monitor mounting bracket, remote control, connection cable, adaptor cable, camera, camera mounting bracket, camera sunshield, extension cable, insulation pad, insulating tape & full fitting instructions.

9635/020

CCD COLOUR CAMERA WITH LED SUPPORT

Includes camera, camera mounting bracket, camera sunshield, extension cable, insulation pad, insulating tape & fitting instructions.

MONITOR SPECIFICATIONS

- 5" Colour TFT LCD monitor
- Two camera inputs (PAL/NTSC)
- Built-in speaker with adjustable volume
- Normal or mirror image function
- Automatic or manual activation

Operating Voltage	11 - 15 V
Power Consumption	up to 8 W
Screen Diagonal	5"/128mm (visible picture)
Resolution	230,000 pixels
Brightness	400 cd/m ²
Operating Temperature	-15°C to +60°C
Humidity	10-95 %
Size (w x h x d)	143 x 125 x 70 mm (inc bracket)

CAMERA SPECIFICATIONS

- Colour CCD camera (PAL)
- Electronic brightness adjustment
- Sturdy, watertight aluminium housing with steel protective cap & adjustable sunvisor.
- Waterproof microphone
- 120° Wide angle lens

Power Consumption	0.2 A
Image Sensor	1/4" CCD J type sensor
Resolution	270,000 pixels
Light Sensitivity	< 1 lux / 0 lux with LED
Operating Temperature	-20°C to +65°C
Vibration Resistance	8 g
Lens	120° diagonal opening angle
Lens Angle (aprox)	h = 90°, v = 70°
Protection	IP67
Size (w x h x d)	92 x 68 x 89