



		RUBBER BONNET FASTENER							
		Rubber hook with steel bracket & clip (see below). Maximum extension from relaxed to tension should be 10%. Hence, the distance between centres 'X & X' should be between 16 - 19 mm.							
		A	B	C	D	E	F	G	H
5301/001	Zinc plated	Weight 50g/1.8oz							
5301/003	Stainless steel								
	METRIC (mm)	54.5	21.0	23.0	20.0	5.00	39.0	10.0	
	IMPERIAL (ins)	2.15	0.83	0.91	0.80	0.20	1.54	0.40	

		CLIP							
		Supplied with 5301 bonnet fasteners (see above).							
		A	B	C	D	E	F	G	H
	METRIC (mm)	31	25	22	12	10	10	4	
	IMPERIAL (ins)	1.22	1	0.87	0.47	0.4	0.4	0.16	



		SPRING BONNET FASTENER							
		Nickel plated, carbon steel. Supplied complete with hook (see below).							
		A	B	C	D	E	F	G	H
4529/002		Weight 41g/1.5oz							
	METRIC (mm)	135	25.4	14.0	63.0	32.0	14.5	13.5	2.00
	IMPERIAL (ins)	5.32	1.00	0.55	2.48	1.26	0.57	0.53	0.08

		HOOK							
		Nickel plated, carbon steel. Supplied complete with 4529/002 bonnet fastener (see above).							
		A	B	C	D	E	F	G	H
		Weight 7g/0.3oz							
	METRIC (mm)	32.0	17.0	12.0	11.0	2.00	21.0	4.20	11.0
	IMPERIAL (ins)	1.26	0.67	0.47	0.43	0.08	0.83	0.17	0.43